Comp/Edit 5410 phototypesetter

Actual, unretouched photo of Comp/Edit screen.

System features

- 12″ CRT screen displays 12 text lines and 2-line revolving function field.
- Scrolling up and down.
- Up to 256 character display repertoire.
- Full editing and correcting capability.
- Three automatic search fields.
- Automatic global search and replace.
- Block move capability.
- Functions displayed at half-intensity.
- Floppy disk stores up to 300,000 characters.
- Automatic file directory, displays file names.
- Merge file capability.
- Format storage.
- Storage and automatic insertion of repetitive alphanumerics and/or commands.
- Typewriter-oriented keyboard.
- Three function-control keypads.
- Operator-selection of justification mode and justification parameters.
- Exception dictionary.
- Automatic compensation for tight lines.
- Automatic ragged composition.
- White space reduction and addition.
- Automatic kerning of operator-selectable character combinations; manual kerning of other combinations.
- Foreground/background operation.
- Automatic tabular composition.
- Automatic insertion of horizontal leaders and rules.
- Automatic insert space.
- 138 type sizes, 16 type styles on-line.
- Unlimited mixing of all 2,208 on-line fonts.
- 70-pica maximum line length.
- 16″ reverse leading; automatic baseline positioning.
- 50-70 lines per minute speed permits input from multiple off-line sources.

Options

- Auxiliary reader for perforated tape input.
- Word processing input by automatic conversion of disk from AM Jacquard word processors.
- General Purpose Interface Port.
- Dual magnetic disks store up to 600,000 characters.
- Telecommunications capability for bi-directional communication with remote phototypesetters, word processors, and computers.
- Proof printer for high-speed production of plain-paper proof before typeset output.

AM Varityper

Comp/Edit 5410
phototypesetter

SPECIFICATIONS

Configuration: Stand-alone phototypesetting system: keyboard, video display, 80K all-RAM memory, magnetic disk storage/retrieval, photo unit.

Keyboard: 49 typewriter-oriented keys, three auxiliary keypads for editing, data management, typographic control.

VIDEO DISPLAY

Screen size: 12″ distortion-free CRT; displays characters equivalent to 18-pt. type with space for accents above upper and lower case characters; green characters on black background; command functions displayed at half-intensity.

Screen text capacity: 12 lines; up to 64 characters per screen line; up to 768 characters total screen capacity.

Function field: Two lines; revolving display of job status.

Character set: Up to 256 upper and lower case alphanumeric characters, function and diagnostic symbols.

Scrolling: Up/down; up to 8,000 characters.

Cursor: Character-size rectangle; unrestricted movement left, right, up, down, home; single and continuous stepping.

Editing: Insert; move; delete of character, word, line, block; overstrike of individual character.

Search: 3 automatic search fields; two by alphanumeric and/or function combinations up to 8 characters; one global search with automatic replace up to 256 characters; multiple searches operator programmed.

Data storage: Up to 99 programmable data storage areas; alphanumerics and/or commands stored and automatically inserted.

COMPUTER MANAGED STORAGE/RETRIEVAL

Storage: Magnetic disk drive; random access magnetic disks; 240 variable length files per disk; 300,000 characters per disk.

Filing system: Each file automatically indexed by file name of up to eight alphanumeric characters.

File directory: File names on disk displayed by operator command.

PHOTO UNIT

Type sizes: 138 on-line type sizes from 5½ to 74 pts. including all whole and half-point sizes; unlimited mixing.

Type styles: 16 type styles on-line; four type discs of four styles each. Unlimited mixing.

Characters: 1,792 characters on-line; 448 characters per type disc.

Character widths: Pre-programmed on type disc; automatically loaded.

Line length: 70-picas maximum in all sizes.

Line spacing (leading): Primary and secondary spacing from 0 to 99½ pts. in ½-pt. increments; also +1 pt. and -1 pt. single-key function, and zero line spacing.

Reverse/advance feed: Up to 16″ in ½-pt. increments; ½ pt. to 999½ pts. per feed.

Reverse carriage: Allows copy to be positioned to left of established left margin.

Output speed: 50 lines per minute (based on 11-pica line, 9-point type); 70 lines per minute proof mode.

Imaging material: Film, grade S paper, or resin coated paper; width to 12″.

SYSTEM FUNCTIONS

Justification: Operator selection of mode; automatic hyphenation with full hyphenation logic, exception dictionary, and discretionary hyphenation; automatic hyphenless; manual. Programmable standards table.

Justification space control: Min./max. allowable justifying word space; max. allowable letterspace expansion; values operator programmable.

Rejustification: Automatic rejustification after editing or entry of new parameters.

Copy positioning: Flush left, right, and centering; automatic by keyboard command.

Mortise: By keyboard command in ½-unit increments; stored value from ½ to 99½-units.

Automatic kerning: Operator-selectable character pairs automatically kerned in ½-unit increments from ½ to 9½ units.

White space control: Reduction and addition of letterspace from ⅛-unit to over 12 units in ⅛-unit increments.

No flash: No-print function for copyfitting purposes.

Zero width: Set characters without escapement for special effects such as overlapping and floating accents.

Tabular composition: Up to 20 tabs within overall measure; copy may be justified, flush left, right, or centered within tabs; each tab can contain separate auto-indent, size, font, line length, copy positioning instructions.

Indent: Automatic indent left, right, center, and hanging.

Ragged composition: Automatic left, right, and center; can be reset to new line endings automatically after entry of new parameters.

Leaders and rules: Automatic insertion of any selected flashable character as horizontal leader or rule; and any selected width value.

Insert space: Automatic insertion of white space (up to 256 insertions per line).

Repeat copy: Automatic repeat of any line/block as many times as required.

Line length remaining indicator: Shows line length remaining in units.

Page depth indicator: Shows accumulation of line spacing in points.

Options:

- ☐ Automatic conversion of disks from AM Jacquard word processing systems.
- ☐ General Purpose Interface Port.
- ☐ Languages: unit can be configured for any one of many available languages.
- ☐ Dual magnetic disk drives.
- ☐ Telecommunications capability.
- ☐ Proof printer.

Electrical: 115V AC 60Hz; 7.5 amps. UL listed, CSA approved.

Environmental requirements: Ambient temperature 50°-90° F; relative humidity 10% to 90%.

BTU/Hr: Approximately 2,360.

Dimensions:	photo unit only	assembled
height	29½″	45″
width	26″	56″
depth	51″	51″
weight		570 lbs.

Specifications subject to change without notice.
©1981 AM International, Inc.
AM, Varityper, Comp/Edit, and Jacquard are registered trademarks of AM International, Inc.

AM Varityper
11 Mount Pleasant Avenue
East Hanover, New Jersey 07936
CANADIAN HEAD OFFICE
165 Milner Avenue
Scarborough, Ontario M1S4G7

For immediate information on Varityper composition systems, call toll-free 800-631-8134 except in Alaska and Hawaii: in New Jersey call 201-887-8000, ext. 666.
In Canada, call 416-298-2700.

AM Varityper

Composed on a Comp/Edit phototypesetter
Litho in USA
A81-9